

## 1 ROUREG™ CONTACT

- Arbeidsstroom
- met Signaleringscontact

GC6

### TECHNISCHE GEGEVENS

<b>Afmetingen h x b x d : 79,8 x 20,5 x 29,5 mm</b>	
Aansluitspanning	Stroomafname
8/12V AC/DC	700 mA
12V DC	200 mA
24V AC/DC	450 mA
24V DC	120 mA
<b>UITSCHAKELING KRACHT :</b>	125V AC - 0,1 A / 12V DC - 2 A



## 1 ROUREG™ CONTACT

<b>SE000246</b>	Elektrische deuropener 1 ROUREG contact 12V AC/DC - arbeidstroom	0,2 kg
<b>SE000249</b>	Elektrische deuropener 1 ROUREG contact 12V DC - arbeidstroom	0,2 kg
<b>SE000250</b>	Elektrische deuropener 1 ROUREG contact 24V DC - arbeidstroom	0,2 kg
<b>SE000251</b>	Elektrische deuropener 1 ROUREG contact 24V AC/DC - arbeidstroom	0,2 kg

## 1 ROUREG™ DIODE CONTACT

<b>SE000261</b>	Elektrische deuropener 1 ROUREG diode contact 12V DC - arbeidstroom	0,2 kg
<b>SE000262</b>	Elektrische deuropener 1 ROUREG diode contact 24V DC - arbeidstroom	0,2 kg



GEINTEGREERDE CONTACT

GEINTEGREERDE BLUSDIODE

**BESCHIKBARE SLUITPLATEN :**

**Bladzijde 13**

